

Mechanical RUBBER™

845-986-2271 • Fax 845-986-0399
www.mechanicalrubber.com

Technical Data Sheet

TYPICAL PROPERTIES OF MR43-60-SB60

SPECIFICATIONS:

SKIRT BOARD
SMOOTH / FILM LINER FINISH

GENERAL PROPERTIES

SBR
60 DUROMETER, SHORE A

TEMPERATURE RANGE:

-40°F TO 176°F

COLOR:

BLACK

TYPICAL RESISTANCES:

ABRASION
ABSORPTION, WATER
ADHESION - METALS
COLD
DIELECTRIC STRENGTH
ELECTRICAL INSULATION
RADIATION
TENSILE STRENGTH

PROCESSES:

SHEETING

APPROVALS:

PHYSICAL PROPERTIES		
PHYSICAL PROPERTY	TEST METHOD	TYPICAL RESULT
DENSITY - DUROMETER	ASTM D1056, ASTM D2240	60±5, SHORE A
TENSILE STRENGTH	ASTM D412	500 PSI
ELONGATION	ASTM D412	200%

The above information is furnished as a guide for selecting materials. Mechanical Rubber disclaims liability for results or use of this information. It is the end user's responsibility to obtain and test samples when determining suitability of material for a particular application.