

Technical Data Sheet

TYPICAL PROPERTIES OF

MR43-60-SB60

TYPICAL RESISTANCES:

ABSORPTION, WATER ADHESION - METALS

ABRASION

SPECIFICATIONS:

SKIRT BOARD

SMOOTH / FILM LINER FINISH

GENERAL PROPERTIES

SBR

80 DUROMETER, SHORE A

TEMPERATURE RANGE:

-40°F TO 176°F

COLD DIELECTRIC STRENGTH ELECTRICAL INSULATION RADIATION

TENSILE STRENGTH

APPROVALS:

PROCESSES:

SHEETING

COLOR: BLACK

PHYSICAL PROPERTIES		
PHYSICAL PROPERTY	TEST METHOD	TYPICAL RESULT
DENSITY - DUROMETER	ASTM D1056, ASTM D2240	60±5, SHORE A
TENSILE STRENGTH	ASTM D412	500 PSI
ELONGATION	ASTM D412	200%
2		
	- 10	
	7 4	
4		
	-	
	3.4	
	7	

MR-F8.5.1I, REV.1; 11/02/2021 MECHANICAL RUBBER



845-986-2271 • Fax 845-986-0399 www.mechanicalrubber.com

The above information is furnished as a guide for selecting materials. Mechanical Rubber disclaims liability for results or use of this information. It is the end user's responsibility to obtain and test samples when determining suitability of material for a particular application.

MR-F8.5.1I, REV.1; 11/02/2021 MECHANICAL RUBBER